



D2648-1 FLAT PATTERN




SECTION A-A




7560 HARDCOAT WELDS
TO WITHIN 0.25 OF
WEARPAD ENDS
0.063 TO 0.125 THICK


SECTION B-B




D2648-3 LONGITUDINAL BEND (MADE FROM D2648-1)



D2648-5 LONGITUDINAL BEND (MADE FROM D2648-1)



D2648-7 LONGITUDINAL BEND (MADE FROM D2648-1)



RELEASED
99.12.20 DS



BREAK ALL SHARP CORNERS 0.063 MAX
MATERIAL: 16 GAUGE AISI 1010-1025 OR ASTM A36/A366 STEEL (0.063 THICK)
FINISH: POWDER COAT GREY (REF. 4.3.5.5) PER DART QSI 005
TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
ALL DIMENSIONS ARE IN INCHES

D	99.11.17	ADDED D2648-7
C	97.06.26	R31.6 WAS R19.6
B	97.05.30	ENLARGE OBROUND, 0.375 WAS 0.250
A	97.03.25	NEW ISSUE
DESIGN	DRAWN BY	DART DART AEROSPACE USA, INC. BELLEVUE, WA
CHECKED	APPROVED	DRAWING NO. D2648
DATE		TITLE WEARPAD
99.11.17		SCALE 1:2